



LINN

KEY FEATURES INCLUDE

- Offers premium levels of stereo, multi-channel audio, and video format processing
- A true system controller solution, not just an AV processor or pass-through pre-amplifier
- Dolby Digital EX, Dolby Pro-Logic II, DTS 96:24 ES, MPEG-2, AAC and Dolby Headphone
- Programmable LinnGo standby button for commonly used or preferred source configuration
- New user interface for simple set-up and control

The KISTO System Controller is one of the most complex and comprehensive products engineered by Linn. With over one hundred connections on the back panel, the KISTO System Controller has been designed to offer a totally comprehensive solution that forms the heart of a high performance home entertainment system. As you would expect from such a comprehensive product, the KISTO System Controller is capable of decoding the majority of current audio and video formats to the highest level of quality.

The product features a new, Linn-designed intuitive user interface for speedier set-up and operation. This interface allows Custom Installation specialists or end-users to add and configure other products with the minimum of effort. The KISTO System Controller also features a sliding front panel that allows access to a number of sockets which can be used for 'infrequent use' products such as a camcorder, games console or PC keyboard.

The front panel of the KISTO System Controller features a new 'LinnGo' standby button which can be programmed to run a variety of configurable macro routines or a preferred start up source configuration. A number of 12 volt triggers at the rear of the product ensure that other elements of a home theatre system including projectors, screens, lighting systems and drapes can also be controlled.

KISTO™ SYSTEM CONTROLLER

SPECIFICATION

A true multi-channel audio and video system controller



1



2



3



4

KISTO™ SYSTEM CONTROLLER

TECHNICAL SPECIFICATION

A true multi-channel audio and video system controller

■ Date of Introduction	Spring 2003	■ Digital Audio Outputs	2 x TOSLINK™ Record Outputs (44.1 / 48 / 88.2 / 96kHz sample rate) 1 x TOSLINK™ Record Output (front panel) (44.1 / 48 / 88.2 / 96kHz sample rate)
■ Type	Audio Video pre-amplifier and System Controller	■ Analogue Audio Outputs	2 x SPDIF phono socket Record Outputs (44.1 / 48 / 88.2 / 96kHz sample rate) 7.1 Phono socket outputs 7.1 XLR Balanced Audio Outputs 1 pair of phono socket Record Output 1 pair of phono socket Record / 2 x SUB Output (configurable) 1 x 1/4" Stereo Headphone Socket (front panel)
■ Size	(H) 140mm (with feet)/(3U high without feet) x (W) 381mm x (D) 384mm	■ Front Panel Interfaces	1 x TOSLINK™ Input 1 x TOSLINK™ Record Output 1 pair of Analogue phono socket Inputs 1 x composite phono socket Input 1 x S-Video Mini-Din socket Input 1 x PS/2 Keyboard Interface 1 x 1/4" Stereo Headphone Socket
■ Weight	7.5kg (unpacked)	■ Audio Decoding	PCM Input 96kHz up sample compatible Dolby Digital EX Dolby Pro-Logic II DTS 96:24 ES MPEG-2 AAC and Dolby Headphone Limbik Party mode PCM MPEG-2 5.1 & 7.1 downmix Adjustable Lip Sync Delay
■ Function	Quality analogue and digital audio pre-amplifier, surround sound decoding, digital and analogue audio conversion and video switching	■ Video OSG Formats	Automatic PAL and NTSC signal detection Automatic Progressive Scan detection
■ Control Interfaces	Remote IR input RC5 input and output Knekt Interface RCU Interface 2 independent RS232 ports Ethernet terminal IR flasher outputs 4 independent +12v trigger outputs 1 PS/2 Keyboard Interface (front panel) 17 button keypad interface 256 x 64 Front Panel VFD Graphical Monochromatic Display	■ User Interface	Menu driven OSG Full Colour OSG Down/up-loadable configurations via RS 232 terminal Internal Help screens
■ Digital Audio Inputs	6 x TOSLINK™ Inputs 6 x SPDIF phono socket Inputs 1 x TOSLINK™ Input (front panel)	■ Power Supply	Switching power supply with auto-ranging (90v to 240v a.c. 50-60Hz)
■ Analogue Audio Inputs	1 pair XLR Balanced Audio Inputs Knekt Interface Input 10 pairs of phono socket inputs (configurable as surround groups) 1 pair of phono socket Inputs (front panel)		
■ Analogue Video Inputs	12 x Composite / 4 x component configurable phono socket inputs 6 x S-Video Mini-Din socket Inputs 1 x component (plus horizontal & vertical sync) BNC Inputs 2 x Scart Input/Output sockets 1 x Composite phono socket Input (front panel) 1 x S-Video Mini-Din socket Input (front panel)		
■ Analogue Video Outputs	3 x Composite / 1 x component configurable phono socket Watch Outputs 3 x Composite / 1 x component configurable phono socket Record Outputs 1 x S-Video Mini-Din socket Watch Output 1 x S-Video Mini-Din socket Record Output 1 x component (plus horizontal & vertical sync) BNC Outputs		

The above information is subject to change without prior notice.

Linn Products Ltd
Floors Road, Waterfoot, Glasgow G76 0EP, Scotland, UK.
Telephone: +44 (0) 141 307 7777, Facsimile: +44 (0) 141 644 4262, Helpline: 0500 888909, E-mail: helpline@linn.co.uk, Website: www.linn.co.uk

Linn Products Inc
8787 Perimeter Park Boulevard, Jacksonville FL 32216, USA.
Telephone: +1 (904) 645 5242, Facsimile: +1 (904) 645 7275, Helpline: 888-671-LINN, E-mail: helpline@linninc.com, Website: www.linninc.com

Linn Deutschland GmbH
Albert-Einstein-Ring 19, 22761 Hamburg, Deutschland.
Telephone: +49-40-890 660-0, Facsimile: +49-40-890 660-29, E-mail: info@linngmbh.de, Website: www.linn.co.uk

Linn Records Ltd
Floors Road, Waterfoot, Glasgow G76 0EP, Scotland, UK.
Telephone: +44 (0) 141 303 5027, Facsimile: +44 (0) 141 303 5007, Helpline/Mail order: +44 (0) 141 303 5029, E-mail: records@linn.co.uk,
Website: www.linnrecords.com

Pack 870 (11/03)